




DALMAX-SG-242423-BEAST 2.0


4.6" [117mm]



GRATE DETAIL



Minimum Length Before Reduction --> see Min Length Chart



SUMP AND GRATE: UNBLOCKABLE SOFA CERTIFIED TO APSP/ANSI/ICC -16 2017, NSF/ANSI/CAN 50 -2020, AND USPC. RPD FIELD CERTIFICATION IS NOT REQUIRED. CORROSION RESISTANT, NON -CONDUCTIVE, NON-MAGNETIC, AND REQUIRES NO BONDING.

SUMP: MOLDED FROM CERTIFIED HIGH -GRADE PVC WITH WATER STOP, 10-IN COUPLING, FEMALE ADAPTOR W/ 10-IN PRESSURE TEST PLUG, AND TWO (2) 2-IN BOTTOM FITTINGS FOR HYDROSTATIC RELIEF VALVES AS PART OF THE MOLDED PRODUCT. THE COUPLING CAN BE REDUCED TO A SMALLER COUPLING AS NEEDED, BASED ON ENGINEERING CALCULATIONS. SEE MINIMUM LENGTH BEFORE REDUCTION CHART. THE MAXIMUM CERTIFIED FLOW MUST NOT BE EXCEEDED. MARKINGS REQUIRED BY LAW ARE IMPRINTED INSIDE THE SUMP REGARDING MANUFACTURER, MODEL NUMBER, SERVICE LIFE AND BORN ON DATE. ACCEPTS SCHEDULE 40 OR 80 PIPING.

GRATE: ONE (1) FLAT 24 -IN X 24 -IN GRATE FORMED OF UV-STABILIZED MOLDED PVC, CERTIFIED TO APSP/ANSI/ICC-16 2017, NSF/ANSI/CAN 50-2020, AND USPC. THE TOP SURFACE OF THE GRATE HAS A TEXTURED DESIGN FOR SLIP RESISTANCE. GRATE SECTIONS ARE 0.20 -IN (5MM) WIDE AND 1-IN (25.4MM) AVG. DEPTH FOR LOAD STRENGTH REQUIREMENTS. SPACE BETWEEN GRATE BARS DOES NOT EXCEED 0.39 -IN (10MM). GRATE PROVIDES A MINIMUM 62% OPEN AREA FOR UNRESTRICTED WATER FLOW. THE MANUFACTURE DATE AND MARKING REQUIRED BY STANDARDS IS MOLDED INTO EACH GRATE.

INSTALLATION: FOLLOW DALDORADO SUPPLIED INSTALLATION INSTRUCTIONS AND WARNINGS. GRATE MUST BE INSTALLED WITHIN SUMP USING ONLY THE 316 SS 1/4" -2 0x1.25" MACHINE SCREWS (TESTED TO APSP/ ANSI/ICC -1 6 2017) AS SUPPLIED BY DALDORADO. NO OTHERS ARE PERMITTED.

CERTIFIED MAXIMUM FLOW RATE:
FLOOR-1734 GPM WALL-1552 GPM

DalMAX-SG-242423 OPTIONS	
TOTAL GPM	1734 FLOOR - 1552 WALL
PORT CONFIGURATIONS	ANY PER NOTES ABOVE
GRATE COLOR	WHITE
MAX PORT SIZE, SIDE	10-IN
MIN PORT SIZE, BUSH DOWN	4 IN

This DALMAX-SG-242423-BEAST sump certified by IAPMO R&T against NSF/ ANSI/CAN Standard 50 for Aquatic Facilities. For indoor and outdoor use. www.IAPMO.com



All drawing are saved in a *.dwg format and are provided as a service to our customers; dimensions supplied by Daldorado are for reference only. Daldorado or any authorized distributor of our products will not be held responsible from files which have been converted and does not warranty the documents against deficiencies or typographical errors of any kind. All measurements of the actual product must be verified before any custom fabrication in the field occurs. COPYRIGHT: This document is the property of Daldorado, LLC and is provided on an in-confidence basis, it may not be copied or reproduced without the permission of Daldorado or its authorized agent.

SUMP LIFE: LIFE OF THE AQUATIC FACILITY
GRATES AND FASTENERS: 25 YEAR SERVICE LIFE/10 YEAR WARRANTY

Product: 24x24x23 Sump & Grate Package

Product #: DalMAX-SG-242423

Material: PVC Rev Date: 06/08/2026

Color: WHITE Rev By: RJG

DALDORADO

2900 Horseshoe Dr. S, Naples, FL 34104
Phone: 888.509.8128
www.daldorado.com