

**COMPOUND WALL WEIR:** FULLY CUSTOMIZABLE WEIR IS CORROSION RESISTANT, NON-CONDUCTIVE, NON-MAGNETIC, AND DOES NOT REQUIRE BONDING. AVAILABLE IN LENGTH UP TO 8-FT, STANDARD CONSTRUCTION OF PVC OR HDPE SHEET MECHANICALLY FASTENED AND STRUCTURALLY BONDED TOGETHER. INTERNAL SUPPORTS ARE INSTALLED FOR STRENGTHENING OVER THE LENGTH OF THE WEIR. STAINLESS STEEL MESH IS MOUNTED TO THE LOWER FRONT FACE FOR APPLICATION OF THE POOL FINISH MATERIAL. PRE-DRILLED PVC MOUNTING TABS ARE AVAILABLE FOR POSITIONING AND LEVELING PRIOR TO CONCRETE APPLICATION. STANDARD PROFILE IS 13-IN HIGH BY 10-IN WIDE, BUT CUSTOM PROFILES ARE AVAILABLE UPON REQUEST. HEAVY DUTY OPTIONS ARE AVAILABLE FOR DIRECT LOADING APPLICATIONS (I.E. WHERE DECK IS POURED ON OR TILE APPLIED DIRECTLY TO TOP OF WEIR INSTEAD OF REINFORCED CONCRETE BETWEEN TOP OF WEIR AND LOAD). OSB CONSTRUCTION COVER AVAILABLE UPON REQUEST.


**PORTS:** FACTORY INSTALLED PORT(S) AVAILABLE AS A SLIP COUPLING OR THREADED FEMALE ADAPTER (PLUGS AVAILABLE FOR HYDROSTATIC TESTING OR WINTERIZATION) IN SCH-40 OR SCH-80 PVC.

**GRATE:** AVAILABLE IN 4-IN, 6-IN, 8-IN, AND 10-IN PARALLEL GRATE FORMED OF MOLDED PVC, CERTIFIED TO NSF/ANSI/CAN 50-2020 AND UV STABILIZED. GRATE OPENINGS DO NOT EXCEED 0.315-IN (8MM) AND COMPLY WITH BS EN 13451 CHILD FINGER AND TOE ENTRAPMENT GUIDELINES. THE GRATE SURFACE BARS RUN PARALLEL TO THE POOL WALL AND PROVIDE 40% OPEN AREA. WEIR GRATING IS NOT FULLY SUBMERGED.

**INSTALLATION:** GRATE MUST BE INSTALLED ACROSS THE OPENING USING ONLY THE 316-SS SCREWS AND CLIPS PROVIDED BY DALDORADO TO SECURE THE GRATE, NO OTHERS ARE PERMITTED.

DalFLOW-WEIR-CMP COMPOUND WALL WEIR			
NOTE: ALL COMPOUND WEIRS REQUIRE A .DWG FILE OF THE CURVE TO BE PROVIDED PRIOR TO FABRICATION			
CONCAVE/CONVEX	CONCAVE		CONVEX
PORT SIZE (INCHES)	2"	3"	4" 6"
PORT TYPE	SLIP COUPLING		FEMALE ADAPTER
PORT SCHEDULE (PVC)	SCH40		SCH80
PORT LOCATION	REAR	BOTTOM	OTHER
PLUG (FOR ADAPTER ONLY)	YES		NO
GRATE SIZE (INCHES)	4"	6"	8" 10"
GRATE COLOR	WHITE	GRAY	BONE
MOUNTING TAB LOCATION	TOP	BOTTOM	NONE
DIRECT DECK LOADING	YES		NO

**NOTES**



All drawing are saved in a \*.dwg format and are provided as a service to our customers; dimensions supplied by Daldorado are for reference only. Daldorado or any authorized distributor of our products will not be held responsible from files which have been converted and does not warranty the documents against deficiencies or typographical errors of any kind. All measurements of the actual product must be verified before any custom fabrication in the field occurs. COPYRIGHT: This document is the property of Daldorado, LLC and is provided on an in-confidence basis, it may not be copied or reproduced without the permission of Daldorado or its authorized agent.

Product:	DalFLOW COMPOUND WALL WEIR		
Product #:	DalFLOW-WEIR-CMP		
Material:	PVC	Rev Date:	07/20/2022
Color:	PER TABLE	Rev By:	Daldorado

**DALDORADO**

4327 Arnold Ave, Naples, FL 34104  
 Phone: 888.509.8128  
 www.daldorado.com